

SAFETY DATA SHEET

CONFORMS TO OSHA HAZARD COMMUNICATION STANDARD (HCS) 29 CFR 1910.1200

Page 1 of 5

Revision Date 6/1/2015 **Supersedes Date** 1/8/2014

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: JAX Dry-Glide (Aerosol)

JAX108 Part number:

1.2 Identified uses: Lubricant where there may be incidental food contact

Uses advised against: Not intended for direct food contact. Other uses advised against may be specified elsewhere in this SDS.

Pressure-Lube Inc. JAX 1.3 Supplier:

> W134 N5373 Campbell Drive Menomonee Falls, WI 53051 USA

Email contact: info@jax.com

Non-emergency

contact:

Phone: 262-781-7660

Fax: 262-781-3906

1.4 Emergency telephone: INFOTRAC:

> North America 1-800-535-5053 Australia 1-300-366-961 Germany 0800-181-2926

International 011-1-352-323-3500 (collect) China 400-120-0761

SECTION 2. HAZARDS IDENTIFICATION

2.1 GHS Classification:

Hazard class(es): Flammable Aerosol Cat. 1; Aspiration Toxicity Cat. 1

2.2 Label elements

Pictograms:



Danger Signal word:

Hazard-determining

components of

labeling:

Naphtha (petroleum), hydrotreated light*

Hazard statements: Extremely flammable aerosol. May be fatal if swallowed and enters airways.

Precautionary

Keep away from heat/ sparks/ open flames/ hot surfaces. - No smoking. Do not spray on an open flame or other ignition statements: source. Pressurized container: Do not pierce or burn, even after use. IF SWALLOWED: Immediately call a poison center/

doctor. Do NOT induce vomiting. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store locked

2.5-10 106-97-8

None

up. Dispose of contents/ container in accordance with local/ regional/ national/ international regulations.

Additional information Not applicable

2.3 Other hazards

Results of PBT and vPvB assessment PBT: Not applicable vPvB: Not applicable

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Composition	<u>Components</u>	<u>%</u>	CAS#	<u>Impurities</u>
	Naphtha (petroleum), hydrotreated light*	50-100	64742-49-0	None
	Propane	10-25	74-98-6	None

3.2 Additional *Contains less than 0.1 % w/w benzene. information

Butane

SECTION 4. FIRST AID MEASURES

4.1 First aid measures

Eye contact: Remove contact lenses, if wearing, and flush eyes with water for at least 15 minutes or until irritation subsides. If irritation

persists, consult a physican.

Skin contact: Remove clothing and shoes, if contaminated. Wash skin with soap and water. Wash or clean contaminated clothing before

reuse and discard oil-soaked shoes. If irritation persists, consult a physician.

JAX Dry-Glide (Aerosol)

Page 2 of 5

Revision Date

Revision Date 6/1/2015 Supersedes Date 1/8/2014

Ingestion:

Never give anything by mouth to an unconscious person. Consult a physician.

Inhalation: Remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention

immediately.

4.2 Most important symptoms and effects, both acute and delayed.

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment available.

No further relevant information available.

SECTION 5. FIREFIGHTING MEASURES

5.1 Suitable extinguishing

media:

Extinguishing media include dry chemical, alcohol foam, and carbon dioxide. Do not use direct stream of water. Water may be used to keep fire-exposed containers cool.

Unsuitable

Do not use direct stream of water.

extinguishing media:

Pressure build-up due to heat exposure may cause containers to rupture. Use water spray to keep containers cool.

5.3 Advice for firefighters:

5.2 Special hazards:

Firefighters should wear full protective gear, including helmet. Use supplied-air breathing equipment for enclosed or confined

space or as otherwise needed.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. Keep away from ignition sources. Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Prevent entry into sewers, waterways or confined areas by diking or impounding. Dike far ahead of spill for later recovery and

disposal. Advise authorities if the product has entered or may enter sewers, watercourses, or extensive land areas.

6.3 Containment and clean-up:

Land spill: Stop leak if you can do so without risk. Recover free product using non-sparking tools. Add sand, earth, or other suitable absorbent material to the spill area. Recover by pumping or with suitable absorbents. Dispose of in accordance with national and/or local regulations relating to waste disposal.

Water spill: Stop leak if you can do so without risk. Confine the spill immediately with booms. Remove from the surface by

skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

6.4 Reference to other sections:

See Section 7 for information on safe handling. See Section 8 for information on personal protective equipment.

SECTION 7. HANDLING AND STORAGE

7.1 Handling: Keep away from heat and direct sunlight. Keep away from ignition sources - Do not smoke. Protect against electrostatic

discharges. Ensure good ventilation/exhaustion at the workplace.

See Section 8.2 for information on occupational hygiene.

7.2 Storage: Store in a cool, dry place in tightly sealed containers. Store out of direct sunlight. Observe official regulations on storing

packagings with pressurized containers. Store away from oxidizing agents. Do not store near heat, sparks, open flame, pilot lights, static electricity, or other sources of ignition. Do not store where temperature may exceed 49°C (120°F). Rotate stock.

See Section 10 for information on conditions and materials to avoid.

7.3 End Uses: Refer to Section 1 for identified uses, and uses advised against.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Workplace exposure

limits:

Naphtha (petroleum), hydrotreated light*

Propane

Components

Butane

Exposure limit and source

Not available Not available

Long-term value = 1810 mg/m³, 750 ppm Short-term value = 1450 mg/m³, 600 ppm

8.2 Exposure controls

Engineering controls: Provide exhaust ventilation or other engineering controls to keep the airborne concentration of vapors below their respective

occupational exposure limits.

Ventilation: Use in a well-ventilated area. See Engineering Controls.

Personal hygiene: Wash skin thoroughly after contact, before breaks and meals and at the end of the work period. Product is readily removed

from skin by waterless hand cleaners followed by washing thoroughly with soap and water.

JAX Dry-Glide (Aerosol)

Page 3 of 5

Revision Date 6/1/2015 Supersedes Date 1/8/2014

Not available

Not applicable

Not an oxidizer

Eye protection: Chemical splash goggles or face shield in compliance with OSHA regulations are advised when eye contact may occur.

Hand protection: Any lined non-permeable rubber gloves.

Respiratory protection: Use with adequate ventilation. Respiratory protective equipment is not normally required where there is adequate natural or

local exhaust ventilation to control exposure. In case of insufficient ventilation, wear suitable respiratory equipment. A

(n-octanol/water):

Explosive properties:

Oxidizing properties:

Autoignition temperature:

NIOSH/MSHA-approved air-supplied respirator is advised in absence of proper environmental control.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Physical and chemical properties

Appearance / odor:Clear with solvent odorVapor pressure:Not availablePhysical state:Liquid and compressed gas in aerosol canVapor density:Not availableOdor threshold:Not availableRelative density:0.65 (typical)

pH: Not available

Melting / freezing point:Not availableSolubility in water:Not availableBoiling point / range:Not availablePartition coefficientNot available

Flash point: Not available; however, product is classified as an

extremely flammable aerosol.

Evaporation rate: Not available **Decomposition temperature:** Not available

Upper flammability limit: Not available

Lower flammability limit: Not available

Percent Volatile: Not available

9.2 Other information No further relevant information available.

SECTION 10. STABILITY AND REACTIVITY

10.1 Reactivity: See sub-sections below.

10.2 Chemical stability: This material is stable under normal conditions.
 10.3 Possibility of Hazardous reactions are not expected to occur.

hazardous reactions:

10.4 Conditions and Avoid high temperatures, sparks and open flames.

materials to avoid:

10.5 Hazardous Carbon monoxide, carbon dioxide.

decomposition products:

11.1 Information on toxicological effects

Acute toxicity / Components LD_{s_0} LC_{s_0}

LD₅₀ and LC₅₀ of Naphtha (petroleum), hydrotreated light* Not available

ingredients:

Propane Not available Not available

Butane Not available 658 mg/l/4h (inhalation, rat)

Routes of exposure: Eyes, skin, ingestion and inhalation

Other information: Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis, which can be

fatal.

SECTION 12. ECOLOGICAL INFORMATION

12.1 Toxicity: <u>Components</u> <u>L(E)C_{so}</u>

Naphtha (petroleum), hydrotreated light*

Propane

Not available

Butane

Not available

Toxicity notes: Not available

12.2 Persistence and degradability: Not available12.3 Bioaccumulative potential: Not available

Page 4 of 5 JAX Dry-Glide (Aerosol)

6/1/2015 **Revision Date Supersedes Date** 1/8/2014

12.4 Mobility in soil: Not available

12.5 Persistence, bioaccumulation

and toxicity for substance(s):

This product is not, or does not contain, a substance that is a PBT or a vPvB.

12.6 Other adverse effects: No adverse effects are expected.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

Consult national or regional authorities for proper disposal and reporting procedures.

SECTION 14. TRANSPORTATION INFORMATION

Dangerous goods descriptions may not reflect package size, quantity, end-use or region-specific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

			Hazard	Packing	
	Proper Shipping Name:	<u>UN Number:</u>	Class:	Group:	Remarks:
U.S. D.O.T.	Aerosols, flammable	UN1950	2.1	None	Refer to Code of Federal Regulations, Title 49 (49 CFR) for additional information on provisions, packaging, and Limited Quantity exceptions.
ADR/RID	Aerosols, flammable	UN1950	2.1	None	Tunnel Restriction D
IMDG	Aerosols, flammable	UN1950	2.1	None	None
IATA	Aerosols, flammable	UN1950	2.1	None	None

SECTION 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture

U.S. Federal Regulations:

SARA Section 302

This product contains greater than 1.0% of the following chemical(s) on the SARA Extremely Hazardous Substances List:

Extremely Hazardous

Substances

None

SARA Section 304 **CERCLA Hazardous** Release of the following chemical(s) at quantities equal to or greater than the reportable quantities (RQ), is subject to

reporting to the National Response Center under CERCLA:

Substances

None

Chemicals

SARA Section 313 Toxic This product contains the following chemical(s) listed in Section 313 at or above the de minimis concentrations:

All components of this material are on the U.S. TSCA Inventory. TSCA Inventory

California Proposition

65 Status

This product does not contain chemical(s) known to the State of California to cause birth defects or other reproductive harm.

California

None

Proposition 65 Listed Components

International Regulations:

European Union: This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. A Chemical Safety Assessment has

not been carried out.

Canada All components are in compliance with the Canadian Environmental Protection Act. This product has been classified in

accordance with the hazard criteria of the CPR and this MSDS contains all the information required by CPR.

Japan MITI Not available Australia Not available **Switzerland** Not available

SECTION 16. OTHER INFORMATION

Sections Revised: New SDS format

Revision Date: 6/1/2015

The information and recommendations contained herein are, to the best of Pressure-Lube Inc.'s knowledge and belief, accurate and reliable as of the date issued. Pressure-Lube Inc. makes no warranty or guarantee, expressed or implied, of their accuracy or reliability, and Pressure-Lube Inc. shall not be liable

Page 5 of 5 JAX Dry-Glide (Aerosol)

Revision Date

6/1/2015 1/8/2014 **Supersedes Date**

for any loss or damage based upon the criteria supplied by the developers of these rating systems, together with Pressure-Lube Inc.'s interpretation of the

*** END OF SDS ***